

## **2021 RWD Figure 8 rules !!!!!**

### CAR PREPARATION

1. All glass and chrome must be removed before entering the grounds. All loose items must be removed from the car including items in the trunk and door panels. Speakers, taillights, door handles, trim, headlights, blinkers, lightbulbs all must be removed. All AIRBAGS MUST BE REMOVED.
2. Door and trunk lids must be welded shut or chained with a minimum 5/16" chain.
3. Hood can be chained with a minimum 5/16" chain or no more than 6,1"inch all thread.
4. Gas tank must be removed. Gas tank is a maximum of 6 gallons and fastened securely in the rear seat area. For driver's safety, a metal tank is mandatory and a cover of some sort over it.
5. Batteries must be moved to the inside of the car and securely Fastened and covered.
6. Air cleaners must be left in place.
7. Driver's door reinforcement must be added. No Grader Blades.
8. Driver's compartment must have a 4-point roll cage. A minimum of 2" OD pipe may be used. Can be welded to the frame.
9. Holes must be cut in the hood large enough for a fire extinguisher to be used.
10. Radiator must be left in place. Electric fans can be used but must be in engine compartment.
11. All wheel and tire balancing weights must be removed. You may run any type of tire you wish. Skidders are allowed.
12. For safety reason, clean engine of oil and grease
13. For safety reason, leave firewall intact and heater cores covered.
14. No AWD CARS.
15. You can run weld in centers.
16. Any make or model of rear-end is allowed.
17. Numbers need to be on a roof sign of some sort.
18. A piece of pipe or square tubing, no more than 4" and no longer than the frame horns can be used for a bumper, front and rear. A push bar can be welded to the bumpers but no taller than 12" and bumper cannot be any wider than the front tires and not extend forward of the car

further than the stock bumper. You can run pipe or tubing from front bumper to rear bumper to tie the car together must stay inside of car not a (exoskeleton).

19. A piece of pipe or sucker rod (maximum 1" diameter) is required from the firewall to the top of the car roof or roll bar to keep the hood from coming into the car.

20. Seatbelt and shoulder harness must be permanently mounted.

21. Drive shaft loop is required.

## **DRIVERS RULES**

1. Helmets with a face shield or goggles must be worn. If a helmet or eye protection comes off or is removed during a race, driver will be disqualified from that race.

2. No profanity on car.

3. Seat belt and shoulder harness must be worn at all times.

4. Hail screen may be placed in the windshield area in front of the driver only.

5. Drivers will be disqualified if any door or hood comes open during that race.

6. Drivers must be present at the driver's meeting held.

7. When call goes out to be in place, drivers have two minutes to be in place or will be disqualified for that race.

8. Any car catching fire will be allowed one restart per race.

9. Any car that rolls over will be allowed one restart per race.

10. All cars must stop immediately when the red flag comes out.

11. Drivers must stay in car until the race is over, except for a fire.

12. Drivers must keep arms and hands inside of car during race.

13. No intentional hits in the center of the track. If an official deems it was an intentional hit u will be disqualified.

14. All cars are subject to reinspection at any time.

15. All rulings by the race official are final.

16. For safety reasons, we recommend that you wear a neck roll.

17. Jeans and long sleeve shirts are mandatory due to insurance reasons.

18. ANY MISCONDUCT IN THE PIT AREA OR ON THE GROUNDS WILL BE GROUNDS FOR IMMEDIATE EJECTION